



# MPM Gear Oil 75W-85 GL-5 FE Premium Synthetic M

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Issue date: 19/11/2019 Revision date: 10/09/2025 Supersedes: 10/09/2024 version: 9.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form	: Mixture
Trade name	: MPM Gear Oil 75W-85 GL-5 FE Premium Synthetic M
Product code	: 18000M
Type of product	: Other engine, gear and lubricating oils.
Product group	: Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses

Main use category	: Professional use, Consumer use, Industrial use
Industrial/Professional use spec	: Non-dispersive use Used in closed systems
Function or use category	: Lubricants and additives

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

MPM International Oil Company BV  
Cyclotronweg 1  
NL 2629 HN Delft, Zuid Holland  
Nederland  
T +31 (0)15 2514030 (08.00 - 17.00 GMT+1)  
[info@mpmoil.com](mailto:info@mpmoil.com), [www.mpmoil.com](http://www.mpmoil.com)

### 1.4. Emergency telephone number

No additional information available

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

#### Adverse physicochemical, human health and environmental effects

No additional information available

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements (CLP)	: P102 - Keep out of reach of children.
EUH-statements	: EUH208 - Contains: Phosphoric acid ester amine salt, Methyl methacrylate. May produce an allergic reaction. EUH210 - Safety data sheet available on request.

### 2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII  
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII  
Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

# MPM Gear Oil 75W-85 GL-5 FE Premium Synthetic M

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

Comments : Highly refined mineral oil, contains <3% (w/w) DMSO extract, according to IP346

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Polysulfides, di-tert-Bu	CAS-No.: 68937-96-2 EC-No.: 273-103-3 REACH-no: 01-2119540515-43	$\geq 1 - \leq 4.5$	Skin Sens. 1B, H317 Aquatic Chronic 3, H412
Phosphoric acid ester amine salt	EC-No.: 931-384-6 REACH-no: 01-2119493620-38	$\geq 1 - \leq 1.9$	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Reaction Products of alcohols, C14-18, C18 unsat., esterified with phosphorus pentoxide and salted with amines, C12-14,-tert-alkyl	CAS-No.: 1471315-74-8 EC-No.: 939-591-3 REACH-no: 01-2119978530-33	$\geq 1 - \leq 1.49$	Aquatic Chronic 3, H412
Magnesium metaborate	CAS-No.: 13703-82-7 EC-No.: 237-235-5 REACH-no: 01-2119976351-35	$\geq 0.1 - \leq 0.99$	Skin Sens. 1B, H317
Methyl methacrylate	CAS-No.: 80-62-6 EC-No.: 201-297-1	$\geq 0.1 - \leq 0.24$	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1B, H317 STOT SE 3, H335

#### Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
Polysulfides, di-tert-Bu	CAS-No.: 68937-96-2 EC-No.: 273-103-3 REACH-no: 01-2119540515-43	(46 ≤ C < 100) Skin Sens. 1B; H317
Phosphoric acid ester amine salt	EC-No.: 931-384-6 REACH-no: 01-2119493620-38	(9.39 ≤ C < 100) Skin Sens. 1; H317 (50 ≤ C < 100) Eye Dam. 1; H318 (50 ≤ C < 100) Eye Irrit. 2; H319
Magnesium metaborate	CAS-No.: 13703-82-7 EC-No.: 237-235-5 REACH-no: 01-2119976351-35	(15 ≤ C < 100) Skin Sens. 1B; H317

Full text of H- and EUH-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

After inhalation : Not required.  
After skin contact : Wash skin with mild soap and water.  
After eye contact : In case of eye contact, immediately rinse with clean water for 10-15 minutes.  
After ingestion : Do NOT induce vomiting. Rinse mouth out with water. Get immediate medical advice/attention.

# MPM Gear Oil 75W-85 GL-5 FE Premium Synthetic M

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 4.2. Most important symptoms and effects, both acute and delayed

After inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
After skin contact	: Not expected to present a significant skin hazard under anticipated conditions of normal use.
After eye contact	: Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
After ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray, powder, foam and CO2.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

No additional information available

### 5.3. Advice for firefighters

Precautionary measures fire	: Exercise caution when fighting any chemical fire.
Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: If spilled, may cause the floor to be slippery.
------------------	---

#### For non-emergency personnel

Protective equipment	: Gloves. Safety glasses.
Emergency procedures	: Do not breathe vapours.

#### For emergency responders

Protective equipment	: Wear suitable protective clothing and gloves. Safety glasses.
----------------------	---

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Detergent. Clean up any spills as soon as possible, using an absorbent material to collect it.
Other information	: Spill area may be slippery. Use suitable disposal containers.

### 6.4. Reference to other sections

No additional information available

# MPM Gear Oil 75W-85 GL-5 FE Premium Synthetic M

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Additional hazards when processed : Avoid all unnecessary exposure. Both local exhaust and general room ventilation are usually required.
- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Handling temperature : < 40 °C
- Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Store in a closed container.
- Storage conditions : Keep container closed when not in use.
- Storage temperature : ≤ 40 °C
- Storage area : Store in dry, well-ventilated area.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### DNEL and PNEC

- Additional information : Based on ACGIH TLV, a concentration of 5 mg/m3 oilspray (TWA, 8 hour workday) is recommended.

#### 8.2. Exposure controls

##### Appropriate engineering controls

##### Technical measures:

No additional information available.

##### Personal protection equipment

##### Personal protective equipment:

Gloves. Safety glasses.

##### Personal protective equipment symbol(s):



##### Eye and face protection

##### Eye protection:

Safety goggles

##### Skin protection

##### Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use

##### Hand protection:

Protective gloves

##### Hand protection

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,4		EN ISO 374

# MPM Gear Oil 75W-85 GL-5 FE Premium Synthetic M

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Respiratory protection

#### Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid.
Colour	: Yellow.
Appearance	: Oily liquid.
Odour	: Characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability (solid, gas)	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 120 °C @ ASTM D92
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 53 mm <sup>2</sup> /s @ 40°C (ASTM D445)
Solubility	: Slightly soluble, the product remains on the water surface.
Log Kow	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 863 kg/m <sup>3</sup> @15°C (ASTM D4052)
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

None under normal conditions.

### 10.2. Chemical stability

Stable under normal conditions of use.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

No naked flames, sparks, and do not smoke.

### 10.5. Incompatible materials

Strong oxidizing agent. Acids and bases.

### 10.6. Hazardous decomposition products

None under normal conditions.

# MPM Gear Oil 75W-85 GL-5 FE Premium Synthetic M

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

##### Phosphoric acid ester amine salt

ATE CLP (oral)	500 mg/kg bodyweight
----------------	----------------------

##### Methyl methacrylate (80-62-6)

LD50 oral	7900 mg/kg
LD50 dermal rabbit	> 5000 mg/kg bodyweight Guideline OECD 402
LC50 Inhalation - Rat (Vapours)	29.8 mg/l/4h
ATE CLP (vapours)	29.8 mg/l/4h

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Not classified  
STOT-single exposure : Not classified

##### Methyl methacrylate (80-62-6)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : Not classified

##### Phosphoric acid ester amine salt

NOAEL (oral, rat, 90 days)	150 mg/kg bodyweight/day @28d (OECD 407)
----------------------------	--

Aspiration hazard : Not classified

##### MPM Gear Oil 75W-85 GL-5 FE Premium Synthetic M

Viscosity, kinematic	53 mm²/s @ 40°C (ASTM D445)
----------------------	-----------------------------

##### Methyl methacrylate (80-62-6)

Viscosity, kinematic	0.561 mm²/s
----------------------	-------------

#### 11.2. Information on other hazards

##### Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

### SECTION 12: Ecological information

#### 12.1. Toxicity

General : This product contains one or more components that have a branched alkylphenol impurity, which is very toxic for aquatic organisms (mentioned in chapter 3). The components containing this impurity, are tested and are not toxic for aquatic organisms. This is why the data from chapter 3 concerning the alkylphenol impurity cannot be used for the classification of the product regarding the aquatic toxicity.

# MPM Gear Oil 75W-85 GL-5 FE Premium Synthetic M

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Polysulfides, di-tert-Bu (68937-96-2)	
EC50 Daphnia 1	63 mg/l @2d
EC50 other aquatic organisms 1	> 100 mg/l @3d
EC50 72h - Algae [2]	> 100 mg/l @3d
EC50 96h - Algae [1]	> 10000 mg/l @0.1d sediment

Phosphoric acid ester amine salt	
LC50 fish 1	24 mg/l @4d Oncorhynchus mykiss
LC50 fish 2	8.5 mg/l Pimephales promelas @4d
EC50 Daphnia 1	91.4 mg/l Daphnia magna
EC50 72h - Algae [1]	6.4 mg/l Selenastrum capricornutum
NOEC chronic fish	3.2 mg/l Oncorhynchus mykiss @4d
NOEC chronic crustacea	0.12 mg/l Daphnia magna @2d
NOEC chronic algae	1.7 mg/l Selenastrum capricornutum @4d

Methyl methacrylate (80-62-6)	
LC50 fish 1	> 79 mg/l Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 Daphnia 1	69 mg/l Daphnia magna
EC50 72h - Algae [1]	> 110 mg/l Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	68 mg/l Daphnia magna Duration: '21 d'
NOEC (chronic)	37 mg/l Daphnia magna Duration: '21 d'
NOEC chronic fish	9.4 mg/l Danio rerio (previous name: Brachydanio rerio) Duration: '35 d'

## 12.2. Persistence and degradability

MPM Gear Oil 75W-85 GL-5 FE Premium Synthetic M	
Persistence and degradability	Not soluble in water, so only minimally biodegradable.

Polysulfides, di-tert-Bu (68937-96-2)	
Persistence and degradability	Rapidly degradable
Biodegradation	13 % @28 d OECD TG

Phosphoric acid ester amine salt	
Persistence and degradability	Rapidly degradable
BOD (% of ThOD)	3.6 % ThOD @28d inherent sediment
Biodegradation	7.4 % Sturm (28d) OECD TG 301B

Magnesium metaborate (13703-82-7)	
Persistence and degradability	Rapidly degradable

Methyl methacrylate (80-62-6)	
Persistence and degradability	Rapidly degradable

# MPM Gear Oil 75W-85 GL-5 FE Premium Synthetic M

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Reaction Products of alcohols, C14-18, C18 unsat., esterified with phosphorus pentoxide and salted with amines, C12-14,-tert-alkyl (1471315-74-8)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

### 12.3. Bioaccumulative potential

#### Polysulfides, di-tert-Bu (68937-96-2)

Log Pow	-
Log Kow	6

### 12.4. Mobility in soil

#### MPM Gear Oil 75W-85 GL-5 FE Premium Synthetic M

Soil	Prevent soil and water pollution.
------	-----------------------------------

### 12.5. Results of PBT and vPvB assessment

#### MPM Gear Oil 75W-85 GL-5 FE Premium Synthetic M

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

### 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The product does not contain any substances with endocrine disrupting properties.

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Additional information : This material and its container must be disposed of in a safe way, and as per local legislation.  
European List of Waste (LoW, EC 2000/532) : 13 02 05\* - mineral-based non-chlorinated engine, gear and lubricating oils

## SECTION 14: Transport information

In accordance with ADR / IMDG

ADR	IMDG
<b>14.1. UN number or ID number</b>	
Not regulated for transport	
<b>14.2. UN proper shipping name</b>	
Not regulated	Not regulated
<b>14.3. Transport hazard class(es)</b>	
Not regulated	Not regulated
<b>14.4. Packing group</b>	
Not regulated	Not regulated



# MPM Gear Oil 75W-85 GL-5 FE Premium Synthetic M

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG
<b>14.5. Environmental hazards</b>	
Not regulated	Not regulated
No supplementary information available	

### 14.6. Special precautions for user

#### Overland transport

Not regulated

#### Transport by sea

Not regulated

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU-Regulations

##### REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)	
Reference code	Applicable on
3(b)	Magnesium metaborate
3(c)	MPM Gear Oil 75W-85 GL-5 FE Premium Synthetic M

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

##### Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

##### Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

##### Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

### 15.2. Chemical safety assessment

No additional information available

# MPM Gear Oil 75W-85 GL-5 FE Premium Synthetic M

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 16: Other information

#### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
ED	Endocrine disruptor
EC-No.	European Community number
vPvB	Very Persistent and Very Bioaccumulative
SDS	Safety Data Sheet
TRGS	Technical Rules for Hazardous Substances
TLM	Median Tolerance Limit
ThOD	Theoretical oxygen demand (ThOD)
STP	Sewage treatment plant
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
PBT	Persistent Bioaccumulative Toxic
OEL	Occupational Exposure Limit
OECD	Organisation for Economic Co-operation and Development
NOEC	No-Observed Effect Concentration
NOAEC	No-Observed Adverse Effect Concentration
LOAEL	Lowest Observed Adverse Effect Level
LD50	Median lethal dose
N.O.S.	Not Otherwise Specified
NOAEL	No-Observed Adverse Effect Level
LC50	Median lethal concentration
IOELV	Indicative Occupational Exposure Limit Value
IATA	International Air Transport Association
IARC	International Agency for Research on Cancer
IMDG	International Maritime Dangerous Goods
EN	European Standard

# MPM Gear Oil 75W-85 GL-5 FE Premium Synthetic M

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Data sources	: Supplier's safety documents. ECHA (European Chemicals Agency).
Training advice	: Normal use of this product shall imply use in accordance with the instructions on the packaging.
Other information	: The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

### Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
EUH208	Contains: Phosphoric acid ester amine salt, Methyl methacrylate. May produce an allergic reaction.
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.